BB 1917R



| Vehicle Dimensions | |
|----------------------------|--|
| Wheel Base (mm) | 5100 - 5900 6700 |
| Load span (ft) | 20 ft 22 ft 24 ft 32 ft |
| Overall Length (mm) | 8600 9400 9815 11995 |
| Overall Width (mm) | 2335 2335 2335 2335 |
| Overall Height (mm) (CBC) | 2600 2600 2600 2600 |
| Front Overhang (mm) | 1335 1335 1335 1335 |
| Rear Overhang (mm) | 2165 - 2580 3960 |
| Ground Clearance (mm) | 270 270 270 270 |
| Cabin | Sleeper |
| Engine | |
| Engine Model | 4D34i |
| Maximum Power, KW | 125 kw @ 250 rpm |
| Maximum Torque, Nm | 520 Nm @ 1400-1600 rpm |
| No. of Cylinders, CC | 4, 3900 |
| Emission Std | Bharat Stage VI |
| Transmission | |
| Gear Box Model & Type | Improved G85, 6F+1R, Mechanical, Synchromesh Gears |
| Clutch Type | Single Dry Plate, Hydraulic Control |
| Clutch Dia, (mm) | 362 |
| Axle | |
| Front Axle | IF 6.0 |
| Rear Axle | MS 145 |
| RAR* | 5.57 (S) / 6.17 (Optional/HPA) |
| Chassis Frame & Suspension | |
| Frame Section | 272x70x6 |
| (D X W X T) (mm) | |
| Front Suspension | Multileaf Spring |
| Rear Suspension | Multileaf Spring |
| Anti-Roll Bar | Front & Rear : Standard for hazards goods pack & High center of gravity pack & 6700WB / Optional (Other) |

| Brakes | |
|----------------------------------|---|
| Service Brake | Pneumatic Foot Operated, Dual Line with ABS |
| Parking Brake | Spring Actuated With Hand Brake Valce @ Cab |
| Front Axle Brake | Ø 410 drum |
| Rear Axle Brake | Ø 410 drum |
| Steering | |
| Steering Type | Hydraulic Power Assisted |
| Fuel Tank & Electricals | |
| Fuel Tank / Filling Capacity* | 215L / 380L (Optional) |
| Adblue Tank | 43L |
| Battery Capacity | 75Ah / 100AH (HAP) |
| Voltage | 24V |
| Performance | |
| Maximum Gradeability % | 23.9% (RAR 5.57) & 26.7% (RAR 6.17) |
| Maximum Geared Speed | 80kmph |
| TCD* | 17.3m - 19.3m 22.6m |
| Tyres (Size, Pattern) | |
| Pattern & Size | 295/90R20 (Tube tyre) / 295/85R22.5 (Tubeless tyre) |
| Weight | |
| Gross Vehicle Weight - GVW (kgs) | 18500 |

Note – This is not OEM leaflet, kindly visit respective OEM website or dealership for updated information.